

TRA-QSFP-100G-CWDM4

100G /CWDM4/ LC Interface

Features

- QSFP28 Multi-Source Agreement compliant (SFF-8636, SFF-8679)
- 100G CWDM4 MSA compliant
- Hot pluggable QSFP28 footprint (SFF-8661)
- Supports 103.125 Gbps Data Rate
- 4x 25.781Gbps Serial Electrical Interface (CAUI-4)
- Dual LC Optical Connector
- 4x uncooled CWDM DFB Transmitters
- 4x PIN Receivers
- Up to 500m Point-to-Point Transmission on Single Mode Fiber
- Operating temperature range 0°C to 70°C
- Power Dissipation <3.5W
- Single +3.3V Power Supply



Applications

- 100 Gigabit Ethernet

Description

TRansceiver.Asia is a high performance QSFP28 transceiver module for 100 Gigabit Ethernet data links over a single mode fibre pair. The maximum reach is 500m. The four transmitters are uncooled CWDM Distributed Feedback (DFB) lasers generating four optical 25Gbps output signals, which are multiplexed together at the optical output port. The four receivers are PIN photodiodes which detect (after optical de-multiplexing) 4x 25Gbps optical input signals.

This transceiver module is compliant with the QSFP28 Multisource Agreement (MSA) and hot pluggable. Always contact **TRansceiver.Asia** commercial agents for compatibility with different equipment platforms.

Optical Interfaces

P/N	Nominal Wavelength [nm]	Protocol	Optical Output Power ¹ [dBm]	Stressed Receiver Sensitivity ² (OMA) [dBm]	Optical Receiver Overload ³ , each Lane [dBm]	Link Length ^{1,4} [Meter]
QSFP-100G-CWDM4	1271/1291/1311/1331	100GBASE	-0.5 to 8.5	≤ -7.3	2.5	≤ 500

Recommended Operating Conditions

Parameter	Min	Typ	Max	Unit	Notes
Storage temperature	-40		85	°C	
Operating Case Temperature	0		70	°C	
Relative Humidity	0		85	%	Non-Condensing
Power Supply Voltage	3.135	3.3	3.465	V	
Power Supply Current			1000	mA	
Power Dissipation			3.5	W	

Transmitter Optical Specifications

Parameter	Min	Typ	Max	Unit	Notes
Data Rate, each Lane		25.78125		Gbps	5
Aggregated Data Rate		103.125		Gbps	5
Total Average Output Power			8.5	dBm	6
Average Output Power, each Lane	-6.5		2.5	dBm	6,7
Launched OMA, each Lane	-4.0		2.5		6,8
Launched OMA minus TDP, each lane	-5.0			dBm	6
Centre Wavelength, Optical Lanes 0 to 3	1264.5	1271	1277.5	nm	
	1284.5	1291	1297.5		
	1304.5	1311	1317.5		
	1324.5	1331	1337.5		
Transmitter and Dispersion Penalty (TDP), each Lane			3.0	dB	
Extinction Ratio, each Lane	3.5			dB	

Receiver Optical Specification

Parameter	Min	Typ	Max	Unit	Notes
Operating Wavelength, Optical Lanes 0 to 3	1264.5	1271	1277.5	nm	
	1284.5	1291	1297.5		
	1304.5	1311	1317.5		
	1324.5	1331	1337.5		
Average Receive Power, each Lane	-11.5		2.5	dBm	9
Receiver Sensitivity (OMA), each Lane			-10.0	dBm	10
Stressed Receiver Sensitivity (OMA), each Lane			-7.3	dBm	11

Pin Function Definition

Pin	Symbol	Description	Pin	Symbol	Description
1	GND	Ground	20	GND	Ground
2	TX2n	Transmitter Inverted Data Input	21	RX2n	Receiver Inverted Data Output
3	TX2p	Transmitter Non-Inverted Data Input	22	RX2p	Receiver Non-Inverted Data Output
4	GND	Ground	23	GND	Ground
5	TX4n	Transmitter Inverted Data Input	24	RX4n	Receiver Inverted Data Output
6	TX4p	Transmitter Non-Inverted Data Input	25	RX4p	Receiver Non-Inverted Data Output
7	GND	Ground	26	GND	Ground
8	ModSelL	Module Select	27	ModPrsL	Module Present
9	ResetL	Module Reset	28	IntL	Interrupt
10	VccRx	+3.3V Power Supply Receiver	29	VccTx	+3.3V Power supply transmitter
11	SCL	2-wire serial interface clock	30	Vcc1	+3.3V Power supply
12	SDA	2-wire serial interface data	31	LPMoDe	Low Power Mode
13	GND	Ground	32	GND	Ground
14	RX3p	Receiver Non-Inverted Data Output	33	TX3p	Transmitter Non-Inverted Data Input
15	RX3n	Receiver Inverted Data Output	34	TX3n	Transmitter Inverted Data Input
16	GND	Ground	35	GND	Ground
17	RX1p	Receiver Non-Inverted Data Output	36	TX1p	Transmitter Non-Inverted Data Input
18	RX1n	Receiver Inverted Data Output	37	TX1n	Transmitter Inverted Data Input
19	GND	Ground	38	GND	Ground

Ordering information

Part Number	Description
TRA-QSFP-100G-CWDM4	QSFP28 CWDM4, CWDM, Tx (DFB), Rx (PIN), maximum distance 500m on SMF, 100 Gigabit Ethernet, dual LC connector, 0°C to 70°C, DDM

Warnings**Process plug**

The transceiver optics is supplied with a dust cover. This plug protects the transceiver optics during standard manufacturing processes by preventing contamination from air borne particles. It is recommended that the dust cover remain in the transceiver whenever an optical fiber connector is not inserted.

Handling Precautions

The transceiver optics is susceptible to damage as a result of electrostatic discharge (ESD). A static free environment is highly recommended. Follow guidelines according to proper ESD procedures.

Laser Safety

The transceiver optics is a Class 1 laser product per international standard IEC 60825-1. Radiation emitted by laser