

## TRA-SFP-1G-160KM

1.25G-EZX Tx 1550nm-160KM,LC Interface

### Features

- 2-Wire Interface Digital Diagnostic Monitoring (SFF-8724)
- Hot pluggable SFP footprint
- 1550nm DFB+APD Laser 160 km SFP
- SFP MSA / IEEE Std 802.3
- Dual LC connector
- 1550nm DFB transmitter
- APD receiver
- 160 km ZX SFP for SMF @ 1.25Gbps
- Operating temperature range 0°C to 70°C or -40°C to 85°C
- Low power dissipation (<1W)
- Digital diagnostics monitoring (DDM)



### Applications

- Gigabit Ethernet
- 1'Fiber Channel
- Other Optical Links

### Description

**TRansceiver.ASIA** is a high performance, TRA-SFP-1G-ZX-160Km is a high performance transceiver module for Gigabit Ethernet data links over two single mode fibers. The maximum reach1 is 160km, with 32dB end of life (EOL) power budget. The transmitter is a 1550nm DFB laser, the receiver is an APD photodiode.

This transceiver module is compliant with the Small Form-factor Pluggable (SFP) Multisource Agreement (MSA) and hot pluggable. Always contact **TRansceiver.ASIA** commercial agents for compatibility with different equipment platforms, Transceiver.ASIA long-reach SFP s are ROHS compliant, allow for real-time diagnostic monitoring as per SFF-8472 and designed to meet Multi-Source Agreement (MSA) standards for Duplex transceivers with LC interface

### Optical Interfaces

P/N	Wavelength	Output Optical Power <sup>2</sup>	Optical receiver Sensitivity <sup>3</sup>	Optical Receiver Overload <sup>4</sup>	Power Budget
					[dB]
TRA-SFP-1G-160KM	1550	0 to 5	≤ -32	-10	≥ 40

## Recommended Operating Conditions

Parameter	Symbol	Min.	Typ.	Max.	Unit	Notes
Power Supply Voltage	Vcc	3.15	3.3	3.45	V	
Power Supply Current	Icc			300	mA	
Case Operating Temperature	Tc	0		70	°C	Standard
		-20		85	°C	Extended
		-40		85	°C	Industrial
Relative Humidity				95	%	
Storage Temperature		-40		85	°C	

## Optical Characteristics

Parameter	Symbol	Min.	Typ	Max.	Unit	Note
<b>Transmitter</b>						
Centre Wavelength	λ	1500	1550	1580	nm	
Ave. output power (Enabled)	P <sub>AVE</sub>	0		5	dBm	1
Side-Mode Suppression Ratio	SMSR	30			dB	
Extinction Ratio	ER	9			dB	
RMS spectral width	Δλ			1	nm	

## Receiver Optical Specification

Parameter	min	typ	max	unit	note
Sensitivity	-37		-10	dBm	6
Receiver Overload	-10			dBm	6
Wavelength of Operation	1260		1600		

## Module Electrical Pin Definition

Pin Number	Name	Function
1	VeeT	Transmitter Ground
2	TX Fault	Transmitter Fault Indication
3	TX_Disable	Transmitter Disable
4	MOD-DEF2	2-Wire Serial Interface Data
5	MOD-DEF1	2-Wire Serial Interface Clock
6	MOD-DEF0	Grounded in Module
7	Rate Select	Not Connected
8	LOS	Loss of Signal
9	VeeR	Receiver Ground
10	VeeR	Receiver Ground
11	VeeR	Receiver Ground
12	RD-	Inverted Received Data Out
13	RD+	Received Data Out
14	VeeR	Receiver Ground
15	VccR	Receiver Power
16	VccT	Transmitter Power
17	VeeT	Transmitter Ground
18	TD+	Transmit Data In
19	TD-	Inverted Transmit Data In
20	VeeT	Transmitter Ground

## Ordering information

Part Number	Description
TRA-SFP-1G-EZX-160KM	1G Single Mode SFP Transceiver, Tx : 1550nm , 160km, LC, DDM, 0°C~+70°C

## Warnings

### Process plug

The transceiver optics is supplied with a dust cover. This plug protects the transceiver optics during standard manufacturing processes by preventing contamination from air borne particles. It is recommended that the dust cover remain in the transceiver whenever an optical fiber connector is not inserted.

### Handling Precautions

The transceiver optics is susceptible to damage as a result of electrostatic discharge (ESD). A static free environment is highly recommended. Follow guidelines according to proper ESD procedures.

### Laser Safety

The transceiver optics is a Class 1 laser product per international standard IEC 60825-1. Radiation emitted by laser